



TE37 SAGA S-plus

BLACK SHADOW LTD.



Matte Translucent Black (PH)

Bring it on!

Spec

Product Name	TE37 SAGA S-plus Black Shadow
Size	18inch/19inch/20inch
Construction Method	Forged 1pc Wheel Knurling finish
Safety Standards	JWL+R Spec 2
Color	Matte Translucent Black (PH)
Included	No.49 EUROPEAN ALUMINUM VALVE RAYS BK

Optional Parts

No.4 VR CAP MODEL-01 LOW BK/SL、 No.57 VR Center Cap Model-01 HI BK/SL、 No.94 VR CAP MODEL-37 BK-Almite、 Vehicle Specific Parts Set

Prices are noted in Japanese YEN(JPY). Specifications in the English version are intended for customers outside of Japan and do not include Japan sales tax.

SIZE	FACE	INSET (): HUB CLEARANCE (mm)	HOLE	P.C.D.	HUB BORE (φ)	DRILL (φ)	PRICE	CALIPER CLEARANCE	DISK PROTRUSIO N (mm)	Load
							PH COLOR			
18x7.5J	F1	48(26)	5	100	65	29-15	102,000	-	1.7	1,543
				114.3	73.1	32-15		∠		
18x8.5J	F2	45(21)	5	100	65	29-15	104,000	-	-	1,543
		42(24)		112	66.6	32-15		AUDI TT(8J), VW GOLF(V /VI/VII/VIII)		
	F1	50(30)		114.3	73.1			∇θη■∠#▲	1.7	
	F2	42(24)				θη■∠		-		
		35(31)				∇θη■∠#△○★				
18x9J	F2	45(28)	5	114.3	73.1	32-15	105,000	∇θη■∠#□▲●	-	2,600
	F3	35(25)								
	F2	50(23)		120	72.6			HONDA CIVIC TYPE-R(FK8,FL5)		
18x9.5J	F3	43(23)	5	100	65	29-15	106,000	▼	-	1,543
		45(21)		114.3	73.1	32-15		θη■∠		
		38(28)						∇θη■∠◎#△○★◆		
		45(21)		120	72.6	HONDA CIVIC TYPE-R(FK8,FL5)				
18x10.5J	F4	15(44)	5	114.3	73.1	32-15	108,000	∇θη■∠◎#△○☆◇	-	1,543
18x11J	F5	13(45)	5	114.3	73.1	32-15	109,000	∇θη■∠◎#△○☆◇	-	1,543

19x8.5J	F1	45(33)	5	112	66.6	32-15	117,000	AUDI A3(8V), A4(8E,8K) ※except 3.2FSI Quattro, MINI CROSSOVER(F60), VW GOLF(VII) ※includes R	1	1,797
	F2	38(24)						114.3	73.1	
		22(34)		ηθ■▲◎■	1					
	F1	42(36)		120	72.6			η▲■	-	
	F2	38(24)						BMW 3er(F30) Fr	-	
				36(26)					BMW 3er.(G20)Rr	
19x9.5J	F2	38(37)	5	112	66.6	32-15	119,000	AUDI A5(8T), BMW 5er.(G30), Z4(G29)Fr TOYOTA GR SUPRA(DB)Fr	-	1,797
	F3	25(23)						114.3	73.1	
		22(26)		η▽▼θ■▲◎#□▲αβ●★◆◆■	1					
	F4	12(41)		120	72.6			HONDA CIVIC TYPE-R(FK8,FL5)	-	
	F1	55(36)						BMW 3er.(F30)Rr, HONDA CIVIC TYPE-R(FK8,FL5)	-	
	F2	45(30)						HONDA CIVIC TYPE-R(FK8,FL5)	-	
36(33)				BMW 5er.(G30)Rr, Z4(G29)Rr, TOYOTA GR SUPRA(DB)Rr	-					
19x10.5J	F4	33(29)	5	112	66.6	32-15	121,000	η▽▼θ■▲◎#□▲αβ●★◆◆■	-	1,797
		22(29)		114.3	73.1			η▽▼θ■▲◎#□▲αβγ○●Ω★◆◆■	-	
19x11J	F4	18(42)	5	114.3	73.1	32-15	122,000	η▽▼θ■▲◎#□▲αβγ○●Ω★◆◆■	-	1,797

20x8.5J	F1	45(34)	5	114.3	73.1	32-15	171,000	η■▲◎■	4.5	1,852
		36(43)						▽▼θη■▲◎#□▲αβγ○●Ω★◆◆■		
		45(34)		120	72.6			TOYOTA ALPHARD(AGH40W)		
		38(41)								
20x9J	F2	27(49)	5	112	66.6	32-15	173,000	AUDI S5(F5CWGL),S7(4GCEUL),Q5(FYDETS), BMW Z4 M40i(G29)Fr., BENZ AMG E43, 4MATIC(W213),CLS450 4MATIC(C257)	1	1,852
		37(39)		114.3	73.1			▽▼θη■▲◎#□▲αβ●◆◆■		
20x10J	F4	15(43)	5	112	66.6	32-15	177,000	BMW M4 Competition(G82), PORSCHE Macan S(95BCTM(A))Rr.	-	1,852
		30(28)		114.3	73.1			η▲◎●◆◆■		

20x10.5J	F4	22(33)	5	114.3	73.1	32-15	179,000	▽▼θη■△◎#▲□αβγ○●Ω★◇◆■	-	1,852
20x11J	F5	15(39)	5	112	66.6	32-15	181,000	BMW M4 Competition(G82)Rr., PORSCHE Macan S(95BCTM(A))Rr.	-	1,852
		10(44)		114.3	73.1			▽▼θη■△◎#▲□αβγ○●Ω★◇◆■		

Caution

※Hub clearance is the measurement used with the standard setting center cap.

* : Tuner size. Sample fitments are for reference only.

[CALIPER CLEARANCE]

▼ : IMPREZA (GDB 4POT)

▽ : IMPREZA (GDB & GRB 4POT)

θ : WRX STI (4POT)

η : WRX STI (6POT)

■ : IS, GS, RC, CROWN (210), MARK-X (3.5L)

△ : IS-F

◎ : RC-F

: SILVIA (S15)

△ : SKYLINE (R34GT-R, CPV35, CKV36, HV37, RV37/400R)

▲ : SKYLINE (R34 GT-R)

□ : SKYLINE (CKV36, HV37, RV37/400R)

α : SKYLINE (CKV36, HV37), FUGA(Y51)

β : SKYLINE (HV37)

γ : SKYLINE (CPV35)

○ : FAIRLADY Z (Z33, Z34, RZ34)

● : FAIRLADY Z (Z34, RZ34)

Ω : FAIRLADY Z (Z33)

☆ : LANCER EVO.(VII~IX, X)

★ : LANCER EVO.X

Σ : LANCER EVO.(VII~IX)

◆ : GT-R (R35/φ380 rotor)

◇ : GT-R (R35/φ380, φ390 rotor)

■ : GR YARIS (RZ)

Ψ : ROADSTER (ND)/124 Spider Brembo

※CALIPER CLEARANCE are for reference only and do not guarantee inspection, and/or the size mandated by local authorities. Selecting sizes is by your own judgement and we recommend consulting fitments with a professional outlet.