



Gram Lights
57CR
LIGHT WEIGHT CONCEPT

Authentic 5spoke sports model.

Spec

Product Name	57CR
Size	15inch/17inch/18inch/19inch
Construction Method	Cast 1pc. Wheel
Safety Standards	JWL+R Spec1
Color	Glossy Black (GX) Gunblue 2 (G2)
Optional	Center Cap, Vehicle Specific Parts Set

Optional Parts

No.14 GL CAP BK/BK、 No.15 GL CAP BK/RD、 No.16 GL CAP BK-Chrome/BL、 No.17 GL CAP Chrome/BL、 No.64 GL CAP BR/RD、 No.63 GL CAP SL/RD、 No.65 GL CAP BK-Chrome/RD、 No.67 GL WR CAP、 No.8 GRAM LIGHTS Spoke Sticker、 Vehicle Specific Parts Set、 No.10 GL RIM STICKER 2S YELLOW/BLACK



Glossy Black (GX)



Gunblue 2 (G2)

Prices are noted in Japanese YEN(JPY). Specifications in the English version are intended for customers outside of Japan and do not include Japan sales tax.

SIZE	FACE	CENTER	INSET (): HUB CLEARANCE (mm)	HOLE	P.C.D.	HUB BORE (φ)	DRILL (φ)	PRICE		CALIPER CLEARANCE	Load			
								GX COLOR	G2 COLOR					
15x8J	-	-	35(24)	4	100	65	29-15	39,000	39,000	-	1,521			
17x7J	-	-	47(26)	4	100	65	29-15	45,000	45,000	-	1,168			
			40(33)							ψ				
			47(26)							-				
			40(33)							ψ				
			47(26)	5	114.3	73.1				29-15	45,000	45,000	-	1,521
			38(35)										-	
			47(26)										-	
			38(35)										-	
17x9J	-	-	38(24)	5	100	65	29-15	47,000	47,000				-	1,521
					114.3	73.1							η≡	
			22(40)										Θη■#▲γΩΣ≡	
18x7.5J	F 1	D 2	40(27)	5	100	65	29-15	51,000	51,000				-	1,521
					114.3	73.1				ηΔ≡				
18x8.5J	F 2	-	37(36)	5	114.3	73.1	29-15	53,000	53,000	▽Θη■Δ#△○☆≡	1,543			
18x9.5J	F 3	-	38(24)	5	100	65	29-15	55,000	55,000	▼	1,521			
						▽Θη■Δ▲α●≡								
			22(40)	114.3	73.1	▽Θη■Δ#△○☆◆≡								
			12(50)											
			38		120	75				HONDA CIVIC TYPE R (FL5/FK8/FK2)*				
18x10.5J	F 4	-	22(31)	5	114.3	73.1	29-15	57,000	57,000	▽Θη■Δ#△○☆◆≡	1,521			
			12(41)							▽Θη■Δ◎#△○☆◆≡				

19x8.5J	F 1	D 1	45	5	112	73.1	29-15	61,000	61,000	BENZ A CLASS(W176)*, BMW X1(F48)*, VW GOLF (V/VI/VII/VIII)※includes R32/R*	1,543
			45(28)		114.3					▽θη■▲◎≡	
		D 2	35(25)		120	75				▽θη■▲◎#○△★◇≡	
		D 1	45(28)							HONDA CIVIC TYPE R(FK8,FL5)	
19x9.5J	F 2	D 2	25	5	112	73.1	29-15	63,000	63,000	AUDI A5(8T)Fr*, BMW Z4(G29)Fr,M4(G82)Fr,TOYOTA GR SUPRA(DB)Fr	1,543
			D 1		45(28)					114.3	
		D 2	35(26)		120	75				▽θη■▲◎#○△★◇≡	
			35							BMW 5er.(F10)*,HONDA CIVIC TYPE R(FL5/FK8/FK2)*	
		D 2	25		BMW M4(F82)Fr*, M3(E92)						
19x10.5J	F 3	D 1	35	5	112	73.1	29-15	65,000	65,000	BMW Z4(G29) Rr*,TOYOTA GR SUPRA(DB) Rr*	1,543
			D 2		22					114.3	
		D 1	35(27)		120	75					
		D 2	12(37)							▽θη■▲◎#○△☆◇≡	
		D 1	35		BMW M4(F82)Rr**						

Caution

5H-P.C.D.112/120: Cannot fit Mercedes Benz (GL Class, GLS Class, R550 4 Matic, R350 4 Matic 2012-, ML63 4 Matic, S550 Plug-in Hybrid, V class (W447), GLE63S 4 Matic, GLE class (V167), EQC400), Rolls Royce, Bentley, Maybach (57, 62, GLS600), BMW X5 (7 seater), X5 (F15), X5 (PHV), X6 Active Hybrid, X7, iX, iX3, Alpina XB7, Audi e-tron, Land Rover, Tesla (Model X), Century (GRG75).

※ * : Tuner size. (Tire and or wheel may interfere or protrude from the body/fender on normal based vehicles.

• Hub clearance is the measurement to the center cap attachment. Measurements will differ depending on the center cap used. Please refer to the option parts tab for more information on center cap clearance.

[CALIPER CLEARANCE]

▼ : IMPREZA (GDB 4POT)

▽ : IMPREZA (GDB & GRB 4POT)

⊖ : WRX STI (4POT)

η : WRX STI (6POT)

■ : IS, GS, RC, CROWN (210), MARK-X (3.5L)

∠ : IS-F

◎ : RC-F

: SILVIA (S15)

△ : SKYLINE (R34GT-R, CPV35, CKV36, HV37, RV37/400R)

▲ : SKYLINE (R34 GT-R)

□ : SKYLINE (CKV36, HV37, RV37/400R)

α : SKYLINE (CKV36, HV37), FUGA(Y51)

β : SKYLINE (HV37)

γ : SKYLINE (CPV35)

○ : FAIRLADY Z (Z33, Z34, RZ34)

● : FAIRLADY Z (Z34)

Ω : FAIRLADY Z (Z33)

☆ : LANCER EVO.(VII~IX, X)

★ : LANCER EVO.X

Σ : LANCER EVO.(VII~IX)

◆ : GT-R (R35/φ380 rotor)

◇ : GT-R (R35/φ380, φ390 rotor)

■ : GR YARIS (RZ)

Ψ : ROADSTER (ND)/124 Spider Brembo

※CALIPER CLEARANCE are for reference only and do not guarantee inspection, and/or the size mandated by local authorities. Selecting sizes is by your own judgement and we recommend consulting fitments with a professional outlet.